
















## ◆ Specification / 規格 【Thru beam type】

Model	Mode	Outline	Detectable object min.	Sensing distance	Amplifier	Operating temperature	Fiber material
FPT-01	M4 x P=0.7 0.5Φ x 1		0.06 φ	120mm	mF-06R or VF-06R	- 25°C ∩ + 70°C	Poly-plastic
FPT-02	M4 x P=0.7 1.0Φ x 1		0.1 φ	320mm			
FPT-03	M3 x P=0.5 0.5Φ x 1 Tube 0.9 φ		0.06 φ	120mm			
FPT-04	M4 x P=0.7 1.0Φ x 1 Tube 1.47 φ		0.1 φ	320mm			
FPT-05	M4 x P=0.7 0.5Φ x 1 Tube 1.47 φ		0.06 φ	120mm			
FPT-06	M3 x P=0.5 0.5Φ x 1		0.06 φ	120mm			
FPT-07	3.0Φ x 15 1.0Φ x 1		0.1 φ	320mm			
FPT-08	4Φ x 15.0 0.25Φ x 1		0.03 φ	60mm			
FPT-09	4x10x15 0.5 φ x 1 Tube 0.9 φ		0.06 φ	120mm			
FPT-10	4x10x15 1.0 φ x 1 Tube 1.47 φ		0.1 φ	320mm			
FPT-11	3x10x10 0.5 φ x 1		0.06 φ	120mm			
FPT-12	4x14x14 1.0 φ x 1		0.1 φ	320mm			
FPT-13	3x13x7 0.5 φ x 1		0.06 φ	120mm			
FPT-14	4x15x7 1.0 φ x 1		0.1 φ	320mm			
FPT-15	M4 x P=0.7 1.0 φ x 1		0.1 φ	320mm			

## ◆ Dimension / 尺寸圖 【Thru beam type】

<p><b>FPT-01</b></p>	<p><b>FPT-02</b></p>	<p><b>FPT-03</b></p>
<p><b>FPT-04</b></p>	<p><b>FPT-05</b></p>	<p><b>FPT-06</b></p>
<p><b>FPT-07</b></p>	<p><b>FPT-08</b></p>	<p><b>FPT-09</b></p>
<p><b>FPT-10</b></p>	<p><b>FPT-11</b></p>	<p><b>FPT-12</b></p>
<p><b>FPT-13</b></p>	<p><b>FPT-14</b></p>	<p><b>FPT-15</b></p>