

## 端子台

		
<b>TBC-10A</b>	<b>TBC-20A</b>	<b>TBC-30A</b>
wire section: 0.75-1.5mm <sup>2</sup>	wire section: 1.5-2.5mm <sup>2</sup>	wire section: 2.5-4mm <sup>2</sup>
rated current: 10A	rated current: 20A	rated current: 30A
voltage: 600V	voltage: 600V	voltage: 600V
wide/high/thick: 8.5/28/25mm	wide/high/thick: 11/32/25mm	wide/high/thick: 11/36/25mm
		
<b>TBC-60A</b>	<b>TBC-100A</b>	<b>TBC-END STOPPER</b>
wire section: 4-10mm <sup>2</sup>	rated current: 60A	
rated current: 60A	voltage: 600V	
voltage: 600V		
wide/high/thick: 22/50/38mm		
		
<b>TBR-10A</b>	<b>TBR20A</b>	<b>TBR30A</b>
wire section: 0.75-1.5mm <sup>2</sup>	wire section: 1.5-2.5mm <sup>2</sup>	wire section: 2.5-4mm <sup>2</sup>
rated current: 10A	rated current: 20A	rated current: 30A
voltage: 600V	voltage: 600V	voltage: 600V
thick/wide/high: 9/42/33mm	thick/wide/high: 11/42/33mm	thick/wide/high: 13/42/33mm
		
<b>TBR60A</b>	<b>TBR-100A</b>	<b>TBD-10A</b>
wire section: 4-10mm <sup>2</sup>	rated current: 100A	wire section: 0.5-1.25mm <sup>2</sup>
rated current: 60A	voltage: 600V	rated current: 10A
voltage: 600V		voltage: 600V
thick/wide/high: 15/42/33mm		thick/wide/high: 8/62/54.8mm
		
<b>TBD-20A</b>	<b>TBR-END STOPPER</b>	
wire section: 0.5-2mm <sup>2</sup>		
rated current: 20A		
voltage: 600V		
thick/wide/high: 9.5/62/54.8mm		

		
<b>TB-1503</b>	<b>TB-1504</b>	<b>TB-1505</b>
wire section: 0.5-1.5mm <sup>2</sup>	wire section: 0.5-1.5mm <sup>2</sup>	wire section: 0.5-1.5mm <sup>2</sup>
rated current: 15A	rated current: 15A	rated current: 15A
voltage: 600V	voltage: 600V	voltage: 600V
wide/high/thick: 46.5/22/17.5mm	wide/high/thick: 55.5/22/17.5mm	wide/high/thick: 63/22/17.5mm
		
<b>TB-1506</b>	<b>TB-1510</b>	<b>TB-1512</b>
wire section: 0.5-1.5mm <sup>2</sup>	wire section: 0.5-1.5mm <sup>2</sup>	wire section: 0.5-1.5mm <sup>2</sup>
rated current: 15A	rated current: 15A	rated current: 15A
voltage: 600V	voltage: 600V	voltage: 600V
wide/high/thick: 73.5/22/17.5mm	wide/high/thick: 103/22/17.5mm	wide/high/thick: 128.5/22/17.5mm
		
<b>TB-2503</b>	<b>TB-2504</b>	<b>TB-2505</b>
wire section: 0.5-2.5mm <sup>2</sup>	wire section: 0.5-2.5mm <sup>2</sup>	wire section: 0.5-2.5mm <sup>2</sup>
rated current: 25A	rated current: 25A	rated current: 25A
voltage: 600V	voltage: 600V	voltage: 600V
wide/high/thick: 55/30/19mm	wide/high/thick: 67/30/19mm	wide/high/thick: 67/30/19mm
		
<b>TB-2506</b>	<b>TB-2510</b>	<b>TB-2512</b>
wire section: 0.5-2.5mm <sup>2</sup>	wire section: 0.5-2.5mm <sup>2</sup>	wire section: 0.5-2.5mm <sup>2</sup>
rated current: 25A	rated current: 25A	rated current: 25A
voltage: 600V	voltage: 600V	voltage: 600V
wide/high/thick: 91/30/19mm	wide/high/thick: 140/30/19mm	wide/high/thick: 163/30/19mm

萬力達電業有限公司  
 泓達電子材料有限公司  
 (03)312-0166